

2E55 Switched Media Converter




The 2E55 Switched Media Converter Module provides fiber optic conversion to and from wire based Ethernet. The Fiber port operates at 100Mbps and the RJ45 port will auto-negotiate its data rate between 10/100Mbps, Full/Half duplex operation. The 2E55 will automatically learn the addresses of the devices connected to each port (up to 1024) and will buffer and route messages accordingly.

Visual (LED) indicators display the status of all ports/links. There is an additional Ethernet port in the module's integrated BUS interconnections. This BUS port provides connection for one additional EOTec 2000 Ethernet Switch or Switched Media Converter Module assisting in forming star or daisy chain network configurations.

SPECIFICATIONS

Mechanical:

Mounting: 35mm DIN Rail
 Weight: < 6oz (170g)



Power Requirements: 10 to 30Vdc @ 200mA, via pluggable cage-clamp screw terminal block
 Ethernet Compliance: IEEE 802.3(U)(X) Compliant, All standard protocols
 Data Rates
 RJ45 Port: 10 or 100Mbps (10/100Base-T(X)), Full Duplex, Automatic wiring correction
 Fiber/BUS Port: 100Mbps (100Base-T(F)X), Full Duplex

Optical Port
 Wavelength: 1300nm
 Connectors: ST compatible (ST is a trademark of AT&T)
 Fiber Type/Size: Multi-Mode fiber; 50 to 100µ core diameter
 Dynamic Range: 9dB

Status Indicators

Power: Green LED; On when proper power is connected
 Port Activity: Green LED; Off when no connection is detected on port
 On with connection to port established
 Flashing to indicate activity on port
 Port Speed (RJ45): Amber LED; Off when data rate is 10Mbps
 On when data rate is 100Mbps

UL 1604
Class 1, Div. 2

Ambient Conditions: -40°C to 85°C Operational
 5 to 95% Relative Humidity Non-Condensing

