

Communication modules (CM)



FBs-CM22



FBs-CM55



FBs-CM25



FBs-CM25C



FBs-CM55E



FBs-CM25E



FBs-CM5R



FBs-CM5H

Model/Item		Specification	Dimension
FBs-CM22		2 RS232 ports (Port3+Port4) with TX, RX indicators	Figure 5
FBs-CM55		2 RS485 ports (Port3+Port4) with TX, RX indicators	
FBs-CM25		1 RS232 (Port3) + 1 RS485 (Port4) with TX, RX indicators	
FBs-CM25E		1 RS232 (Port3) + 1 RS485 (Port4) with Ethernet interface and RUN, LINK, TX, RX indicators	
FBs-CM55E		2 RS485 ports (Port3+Port4) with Ethernet interface and RUN, LINK, TX, RX indicators	
FBs-CM25C		General purpose optical isolation RS232↔RS485 converter, with RX indicators	Figure 4
FBs-CM5R		General purpose optical isolation RS485 repeater, with RX indicators	
FBs-CM5H		General purpose optical isolation four ports RS485 Hub, with ACT, COLLISION indicators	
RS232 Specification	Mechanism	DB-9F standard plug	
	Electric	EIA RS232 standard specifications	
RS485 Specification	Mechanism	3-pin European plug-able terminal block	
	Electric	EIA RS485 standard specifications with built-in termination resistor	
Ethernet Specification	Mechanism	4-pin European plug-able terminal block	
	Electric	10BaseT, IEEE 802.3 standard	