

EX9188 SERIES

Internet/Ethernet Communication Controller

EX9188E8D



Feature & spec:

(OEM/ODM)

- EX9188E8D: Support 7 RS232/RS485 devices
- Ethernet port for TCP/IP features: TCP, UDP, IP, ICMP, ARP, RARP
- COM1: Can be used to download program and can be RS232 port
- COM2: 3000V Isolation
- Dual Watchdog support for system recovery
- CPU: 80188, 40MHZ
- SRAM: 256KB
- FLASH ROM: 512KB
- EEPROM: 2KB
- EMBEDDED OS: RomDOS(Datalight®)
- Advantech / ICP compatible
- Series: EX9188E1, EX9188E2, EX9188E3, EX9188E4, EX9188E5, EX9188E8
- Operating Temp: -25~+75°C

Model No.	EX9188E1D	EX9188E2D	EX9188E3D	EX9188E4D	EX9188E5D	EX9188E8D
Ethernet port	10 BASE T	10 BASE T	10 BASE T	10 BASE T	10 BASE T	10 BASE T
COM1	RS232(5wire)	RS232(5wire)	RS232(5wire)	RS232(5wire)	RS232(5wire)	RS232(5wire)
COM2	X	RS485(Isolate)	RS485(Isolate)	RS485(Isolate)	RS485(Isolate)	RS485(Isolate)
COM3	X	X	RS232(3wire)	RS232(3wire)	RS232(3wire)	RS232(3wire)
COM4	X	X	X	RS232(3wire)	RS232(3wire)	RS232(3wire)
COM5	X	X	X	X	RS232(3wire)	RS232(3wire)
COM6	X	X	X	X	X	RS232(3wire)
COM7	X	X	X	X	X	RS232(3wire)
COM8	X	X	X	X	X	RS232(3wire)

Table I