VT320D



FEATURES

- Bright Active Matrix TFT Display
- → 30-93kHz Horizontal Scan
- 1366 x 768 Max. Resolution
- Digital or Analog Interface
- Wide Viewing Angles
- Deluxe Table Stand (optional)
- 550 nits Brightness
- Multiple Video Input Selections
- Aspect Ration: 16:9
- *Supports all VESA standard video formats

CONTACT

HEADQUARTERS

11529 Sun Belt Ct. Baton Rouge, Louisiana 70809

Phone 800,223,8050 International 001.225.298.0300 Fax 225.297.2440

E-mail

sales@vartechsystems.com www.vartechsystems.com

Website

Solutions for Demanding Applications



32.0" WXGA Tabletop Mount LCD Monitor

This 32" tabletop flat panel display is designed to be placed in a variety of public information, industrial and process control environments requiring a large tabletop display that supports resolutions from VGA to 1366 x 768 resolutions and NTSC/PAL video. The display is auto sync compatible with most PC's video standards, and can be integrated into a wide variety of industrial control and man-machine interface applications.

SPECIFICATIONS

Display Size

32.0 Inch

Panel Type

TFT Active

Resolution Capabilities

1366X768

VGA to WXGA

Pixel Format

640x480, 800x600, 1024x768, 1280 x 1024,1366x768*

Pixel Pitch

.519mm (w) x .173 mm (h)

Viewing Angle

Left / Right: 85º/85º Up / Down: 85°/85°

Active Display Area

27.912" (w) x 15.693"(h) 708.954 mm x 398.592 mm

Contrast Ratio

1000:1 Typical

Brightness

550 Nits Typical

Backlight

40,000 Hours Typical

Colors Supported

16.7 M

Input Connectors

HD15(F), DVI-D, S-Video, CVBS, Component

Video Input

0.7Vp-p / 75 ohm, Digital NTSC/PAL

TTL Separate H&V

Power Source

100-240 VAC

Power Consumption

180 Watts

20 Watts Sleep Mode

Temperature

Operating: 0° to 40°C Storage: -20° to 60°C

Humidity

Operating: 5 to 90% NC Storage: 5 to 95% NC

Altitude

Operating: up to 10,000 ft. Storage: up to 40,000 ft.

Response Time

8msec typical 12msec maximum

Dimensions (Actual)

31.11" (w) x 18.91" (h) x 3.27"(d)

790.2mm x 480.2mm x

82.97mm

Weight (Actual)

44.09lbs / 20kg

Standards

UL, CE, TUV, FCC Cert.

OPTIONS

- 100mm/200mm VESA Mounting
- Deluxe table stand

www.vartechsystems.com