PC104 Page 1 sur 1

EX-9385 PC104 3869X



Click for larger photo

## **Key Specifications/Special Features:**

- CPU+Chipest : ALI M6117C single chip with on-chip 386SX-40 CPU
- I/O Chipset :SMC37C669 I/O chipset
- BIOS: AMI BIOS, 128KB (Flash) EPROM
- DRAM: 4MB soldered on board
- I/O setup built in BIOS
- Bus Type: PC/104 Connector
- DOC socket: 32-pin socket for DiskOnChip SSD 8MB ~ 288MB
- Speaker: Buzzer on Board
- CMOS Backup: Backup by Li battery
- PS/2 Keyboard: 5-pin header
- PS/2 Mouse: 6-pin header
- IDE Interface: support one port up to 2 x IDE devices
- FDD: Two 3 1/2" or 5 1/4" FDD, Drives A, B swappable
- Parallel Port: One bi-directional SPP/EPP/ECP parallel port configured as LPT1,2,3
- Serial Port x 4: 4 x 16-byte FIFO 16C550 RS-232.Jumper selectable RS-232 x 3 + RS-

232/422/485 x 1

- Watchdog Timer: 1/2/4/8/16/32/64/128/256/512 sec.
- Miscellaneous Connectors/Jumpers: Reset, HDD LED, 2-pin single +5V connector for

external power

- Power Requirement: Single +5V power by using 2-pin connector
- Dimension: 95mm x 90mm PC/104 form factor
- Operating Temperature: 0 60°C (140°F)

## **Main Export Markets:**

Worldwide